

SGCCTV®





















- 1. Ambarella A7LA50 chipset, 5MP CMOS sensor
- 2. Dual removable batteries 2000mAh/pcs 2pcs
- 3. Last recording time is 11 hours
- 4. 5MP 2560 X 2160 video resolution
- 5. 45MP photo resolution
- 6. GPS location function
- 7. IP66 waterproof
- 8. Encryption passwords protect firmware
- 9. 2 meters drop testing
- 10. AV in and HDMI and USB interface
- 11. 140 degrees view angle lens
- 12. PTT/external camera/remote control/charging dock support

| Model: CCBWV8GPS | Specifications |
|-------------------------|--|
| Camera Angle | 140° |
| Video Format | MOV/MP4/AVI |
| Storage Capacity | Built-in 16G/32G/64G/128G |
| GPS | Yes |
| Digital Zoom | 16 times (The maximum resolution cannot be adjusted) |
| Video Resolution | 5MP 2560x2160 30P 2304x1296 30 P 1920x1080 30P 1280x720 60P/30P 848X480 60P/30P |
| Compatible System | Windows (98/2000/ME/XP/7/8/10), Note: Win 8/10 needs to be set to disable digital signature |
| One touch record | One-touch recording (in the off state, press the "Video" button directly to enter the recording mode) |
| Display Size | 2-inch LCD full HD display, diagonal ≥ 51mm |
| Loop Recording | Support (when the memory is full, the system automatically deletes the first recorded video |
| Overlay Watermark | Support |
| Fast | Support 2-128 times fast forward and rewind |
| Native Playback | Support (on-site playback of video/photo/audio files) |
| Pre-recorded / extended | Support (Default resolution pre-recorded for 30 seconds, extended recording can be set) |
| One-click playback | Support (One-click playback of the latest recordings) |
| Photo Format | JPEG |
| Segmented Video | Support (Multiple time-segmented videos can be set) |
| Photo Pixel | 5M (2560x1920) 8M (3200x2400) 12M (4000x3000) 16M (4608x3456) 33M (7696X43 29) |
| Slide | Electronic Image Stabilization |
| Anti-Shake | Electronic shutter |
| Shutter | Automatic |
| Audio | WAV |
| One-click | Support separate recording, dual microphone noise reduction |
| Infrared | 10 meters to see face, 15 meters to see human silhouette |
| Key Mark | Support (One-click mark highlight video when shooting video) |
| Night Vision | Manual Switching |
| Password Protection | Support (Software password protection, tamper-proof) |
| Battery | 1950mah x2pcs |
| Log | Support (Documents are attached time, product number, user) |
| Charging | ≤4 hours |
| Motion Detection | |
| Recording Time | Support (Screen object movement, automatically turn on recording mode) Two batteries can record around 11 hours |
| Voice | Support (Can be equipped with a dedicated car suction cup for driving recorder) |
| | |
| Weight | 155g + 15g (Host + back clip) |
| Car Mode | Automatic |
| Physical Dimension | 85x62x31mm |
| Alarm Support | (Long Press he menu button to activate the alarm sound and alarm flash) |
| Protection Level | IP64 |
| Laser Positioning | Support (Positioning shooting, keep the screen from shifting) |
| Anti-drop rating | 1.5m |
| Flashlight | Supports (Lights and fill lights at night) |
| Working temperature | -30°C ~ 55°C |
| Interface | 14Pin multi-function interface, HDMI high-definition interface, USB data charging |